# MAGELLAN™ 9900i

### **CDATALOGIC**

## Scanning Excellence with an AI Edge



#### THE NEXT GENERATION IS HERE

The #1 selling "in counter" scanners for assisted and self check-out are now even better. Fresh styling, rugged design, industry-leading scan performance and new options that enable Artificial Intelligence (AI) at the check-out put the Magellan 9900i portfolio in a class of their own.

In 2013, Datalogic established a unique scanner style with our 2.7 in / 6.8 cm tower (bonnet), and the 9900i continues to support that popular form factor. The lower height allows customers to better meet ADA compliance and improve the customer experience. Three chassis lengths, multiple check stand mount options and the addition of a Top Down Reader (TDR) allows customers to tailor a solution that best solves their assisted and self check-out needs.

With basic and advanced configurations, the 9900i scanners and scanner/scales are the perfect companion for Point of Sale (POS) systems in all high throughput checkout environments.

### ENHANCING THE CASHIER OR CUSTOMER EXPERIENCE

Packed with the latest imaging technology, the 9900i scanners feature the largest scan volume in their class. This ensures fastest read rates and ease of use regardless of 1D, 2D, GS1 or Digimarc symbologies.

The new Magellan scanners feature capacitive touch buttons and smooth surfaces to ensure the above counter areas are easy to clean and sanitize.

The coming 9900i TDR option expands the scan volume by 20% and adds an industry unique sixth sided view of items crossing the platter for the ultimate scanning experience. The TDR comes in 3 heights and offers an optional integrated customer-facing reader, enabling customers to scan mobile devices and coupons independent from a cashier in assisted lanes improving efficiency.

The Magellan 9900i scanners feature capacitive touch buttons and smooth surfaces to ensure the above counter areas are easy to clean and sanitize.

### FEATURES FOR TODAY AND THE FUTURE

Magellan 9900i is powered by QuadVision™, a multi-core processor and multi-camera system with embedded Linux operating system to future-proof the platform. ScanSentry™ color camera options and neural processors coming in 2023 will result in a check-out that is fully enabled to support Artificial Intelligence (AI) software that will boost customer satisfaction and improve loss prevention.

### **FEATURES**

- 2.7" / 6.8 cm tower height allows layout flexibility at the checkstand or SCO.
- Magellan 9900i features QuadVision™, a powerful IMX8 multi-core processor utilizing
   4 cameras (2 horizontal and 2 vertical) that brings world class compute performance to
   the scanner. The 9900i delivers multiple high resolution images for each scan. Combine
   the powerful processors, 5 sided image capture and Datalogic's legendary software
   and you have previously unheard of performance to decode the most difficult and/or
   damaged barcodes. In addition, future optional integrated color cameras and color TDRs
   can be used for machine learning image capture and simultaneous video streaming via
   USB 3.0 for loss prevention.
- Optional built-in neural processors and accelerators enable trillions of operations per second inside the scanner eliminating a need for extra servers or cloud connections at the checkout.
- Note that the performance has already been optimized for the future GS1 Digital Link symbology which links valuable manufacturing and health safety details to each transaction. However GS1 final decode is subject to update during pilot testing.

## INTEGRATED LOSS PREVENTION

### ScaleSentry Technology

- Monitors the 2 primary sides of the scale platter with an infrared (invisible) beam to detect if fruit or produce is misplaced on the scale platter causing the item to be under-weighed.
- Misplaced fruits or produce will break the infrared beam and trigger an alert to the cashier, preventing the weight from being transmitted to the POS until the cashier corrects the problem.

### All-Weighs™ Scale Platter

 The All-Weighs scale platter design provides an alternative weighing surface on top of the bonnet, allowing the user to lay produce that is too long to fit on the platter.



### MAGELLAN 9900i (Scanner only: 9910, 9911, 9912; Scanner/Scale: 9921, 9922)

## TECHNICAL SPECIFICATIONS

DECODING CAPABI	LITY	PHYSICAL CHARAC	TERISTICS
Auto Discriminates all Retail Barcodes	EAN/JAN/UPC, Code 128, EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked Omnidirectional; MicroPDF417; PDF417; UPC A/E Composites. Aztec Code; Data Matrix; QR Code, Micro QR, Digimarc® Barcode and all future GS1 codes.	Dimensions	Depth (Below Counter): 10.6 cm / 4.0 in Length: Short - 35.2 cm / 13.9 in Length: Medium - 39.9 cm / 15.7 in Length: Long - 43.7 cm / 17.2 in Width: 29.2 cm / 11.5 in 9900i Height (Above Counter): 6.8 cm / 2.7 in
Illumination	Multiple diffused LEDs: orientation and wavelength optimized for eye comfort.	ELECTRICAL	Scanner Power Consumption: 12 VDC
Scan Indicators	Visual: Good Read confirmation for all reading planes Audio: 85 dB Speaker - Adjustable Tone and Volume plus Supports WAV file formats.	Power Requirements	Operating (Nominal): 9.3 Watts; Sleep: 7.3 Watts; Optional DC brick: AC Input: 100 - 240 VAC, 50-60 Hz Optional Ethernet 48 VDC brick: AC Input: 100 - 240
COMMUNICATIONS			VAC, 50-60 Hz
Host Multi-Interface	RS-232 / USB Multi-Interface: OEM (IBM) USB Plus Power (Scanner / Scale); RS-232 (Scanner) / RS-232 (Scale); RS-232	ENVIRONMENTAL	
		Ambient Light	0-86,080 lux
	(Scanner) or Single Cable RS-232 (Scanner / Scale)	ESD Protection	25 kV air discharge
POS Operating Systems	Windows10, Linux, 4690, Android™;	Humidity (Non-Condensing)	5 - 95%
Auxiliary Ports	OPOS and JavaPOS Utilities are available for download Powered USB Host (Type A) (x2); Powered RS-232;	Temperature	Operating: 10 to 40 °C / 50 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F
	Remote Scale Display; EAS Controller Ports; Sensormatic, Interlock	SAFETY & REGULA	TORY
Ethernet Ports	1 x Ethernet is standard; Optional 7 port Ethernet switch (IEEE1588) NOTE: Switch requires an external 48V power supply	Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.  See Quick Reference Guide for a complete list of certifications.
OPTIONAL SCALE FEATURES			Complies to China RoHS; Complies to EU RoHS;
Magellan Dual Interval Scale Technology	Minimum Increment: Range 1: 0.002 kg / 0.005 lb; Range 2: 0.005 kg / 0.010 lb Scale Capacity: Range 1: 0 - 6.0 kg / 0 - 15.0 lb;	Environmental Compliance	Complies to R.E.A.C.H EC1907/2006
		UTILITIES	
Magellan Single Interval Scale Technology	Range 2: 6.0 - 15.0 kg / 15.0 - 30.0 lb	Aladdin™ Configurator	Datalogic Aladdin provides customers the opportunity to manage the configuration of handheld or fixed position products, and allows firmware updates, advanced formatting through an intuitive user interface
Adaptive Scale	Compatibility – Adaptive Scales: Bizerba; Mettler Toledo; Max. Static Weight: 68.0 kg / 150.0 lb Vibration immunity: 4 filter settings	Magellan SDK(s)	Datalogic will provide developer tools to support POS integration and the optional AI enablement HW functionality (Color cameras, Neural Processors, and
LOSS PREVENTION			Ethernet expansion).  Current Diagnostic Reporting utilizes WMI (OPOS and
All-Weighs Scale Platter	Integrated horizontal and vertical scale platter surfaces increase active weighing area for easy, accurate weighing of large items.	Remote Management Capabilities	JavaPOS) and MBeans (JavaPOS); Host Download Supports IBM Director, Wavelink Avalanche™ and other ERP management solutions.
ScaleSentry	ScaleSentry is an infrared platter detection system to provide shrink prevention; Configurable audio / visual indicators identify items placed outside weighing surface	FUTURE AI ENABLE	EMENT FEATURES (OPTIONAL)
		Image Capture	Magellan 9900i offer two integrated color cameras for Al inference models such as produce / item recognition (integrated horizontal plus the TDR).
EAS Features	Integrated EAS Antenna for Checkpoint and Nedap. Sensormatic Deactivation Controller integrated with Datalogic SmartSentry™ technology; Scanner provides Good Read / EAS Status Indicators	Neural Processors	Magellan 9900i color cameras have integrated neura processors.
		Tensor Processor	Magellan 9900i offer a Coral TPU for AI inference model acceleration inside the scanner.
		WARRANTY	
		Warranty	1-Year Standard Factory Warranty (5 day turn around

## **ACCESSORIES**



90ACC0419 Top Down Reader (TDR ) 31.5 cm / 12.4 in 90ACC0418 Top Down Reader (TDR ) 22.8 cm / 9.0 in 90ACC0417 Top Down Reader (TDR ) 17.8 cm / 7.0 in Top Down Reader with Customer Facing Reader also available



90ACC0340 Single Display/ Single Interval



90ACC0343 Dual Display/ Single Interval



Smart Color Cameras (coming soon)

© 2022-2023 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • Cashier Training, Produce Rail, SmartSentry, ScaleSentry, and Productivity Index Reporting are trademarks of Datalogic S.p.A. and/or its affiliates. • All other trademarks and brands are property of their respective owners. • Product specifications are subject to change without notice. • DS-MAGELLAN-9900i-EN. Revision C. 20230511